

GNWQ Cutting Submersible Sewage Pump

Submersible sewage pump with a hardened alloy cutter that shreds rags, wipes, fibre and plastic on intake — no clogging.

KEY FEATURES

- 48 HRC hardened alloy cutter disc (twin / triple / spiral blade)
- Heat-treated 3Cr13 semi-open impeller — wear-resistant, rust-free
- Detachable cutter disc (municipal or livestock pattern)
- Cast iron (HT200/250) or precision-cast SS304 body
- Single-phase 220 V available on small models

APPLICATIONS

- Municipal & building sewage, basements, high-rise
- Farms, slaughterhouses, biogas tanks
- Textile, food, chemical & industrial wastewater



MODEL SELECTION TABLE

Model	Flow (m ³ /h)	Head (m)	Power (kW)	Voltage (V)	Outlet (mm)
50GNWQ10-10-0.75	10	10	0.75	220/380	50
50GNWQ12-10-1.1	12	10	1.1	220/380	50
50GNWQ15-15-1.5	15	15	1.5	220/380	50
65GNWQ20-10-1.5	20	10	1.5	220/380	65
50GNWQ20-15-2.2	20	15	2.2	380	50
65GNWQ25-15-2.2	25	15	2.2	380	65
80GNWQ35-12-2.2	35	12	2.2	380	80
50GNWQ25-16-3	25	16	3	380	50
50GNWQ15-20-3	15	20	3	380	50
65GNWQ35-16-3	35	16	3	380	65
80GNWQ35-15-3	35	15	3	380	80
50GNWQ25-22-4	25	22	4	380	50
65GNWQ35-18-4	35	18	4	380	65
80GNWQ50-18-4	50	18	4	380	80
100GNWQ60-12-4	60	12	4	380	100
65GNWQ40-20-5.5	40	20	5.5	380	65
80GNWQ60-16-5.5	60	16	5.5	380	80
100GNWQ70-15-5.5	70	15	5.5	380	100
65GNWQ40-25-7.5	40	25	7.5	380	65
80GNWQ80-20-7.5	80	20	7.5	380	80

Model	Flow (m³/h)	Head (m)	Power (kW)	Voltage (V)	Outlet (mm)
100GNWQ100-15-7.5	100	15	7.5	380	100
150GNWQ120-10-7.5	120	10	7.5	380	150
100GNWQ120-18-11	120	18	11	380	100
150GNWQ150-15-11	150	15	11	380	150
100GNWQ150-18-15	150	18	15	380	100
150GNWQ200-15-15	200	15	15	380	150
150GNWQ180-20-18.5	180	20	18.5	380	150
200GNWQ250-15-18.5	250	15	18.5	380	200
150GNWQ200-20-22	200	20	22	380	150
200GNWQ300-15-22	300	15	22	380	200

Precision-cast SS304 versions (GNWQ-S) available across the range. Specifications for reference; confirm final duty point with our engineers.