

Wilden Air-Operated Diaphragm (AODD) Pump

AUTHORIZED DEALER · 100% GENUINE · IN STOCK

Genuine Wilden® air-operated double-diaphragm pumps — sealless, self-priming and run-dry safe, for corrosive, viscous and solids-laden fluids. Pumps and spare parts in stock.

KEY FEATURES

- 100% genuine Wilden, supplied as an authorized dealer
- Sealless, self-priming; run-dry and deadhead safe
- Air-driven — spark-free, no electricity (ATEX-suitable)
- Pro-Flo® SHIFT air-saving option lowers running cost

APPLICATIONS

- Chemicals & acids, electroplating, wastewater
- Food, beverage & pharma (Saniflo hygienic)
- Mining slurry (Turbo-Flo), paint, ink & adhesives



MODEL RANGE (METAL & PLASTIC)

Model	Port (inch / mm)	Max Flow (L/min)	Max Flow (gpm)
Wilden P.025	1/4" / 6 mm	~14	~3.7
Wilden P.100	1/2" / 13 mm	~53	~14
Wilden P.200	1" / 25 mm	~160	~42
Wilden P.400	1-1/2" / 38 mm	~360	~95
Wilden P.800	2" / 51 mm	~567	~150
Wilden P1500	3" / 76 mm	~1040	~275
Wilden T15 (PTFE)	1-1/2" / 38 mm	~360	~95

GENERAL SPECIFICATIONS

Max air inlet pressure	8.6 bar (125 psi)
Max discharge head	up to ~86 m
Drive	Compressed air (no motor)
Series	Original, Advanced, Pro-Flo SHIFT, Turbo-Flo, Saniflo

MATERIALS

Body	Aluminium, cast iron, SS316, Alloy C, PP, PVDF, PTFE-fitted
Diaphragm	PTFE, Santoprene, Buna-N, Viton, EPDM, Neoprene

Flow figures are typical maximums for reference. Available in the full range of Wilden metal and plastic models and materials.

For other models, sizes, materials or exact performance data, please contact us.

www.haquanpump.com sales@haquanpump.com